<u>KMT2-11 MECHANICS TRUCK</u> (25,999-33,000 GVWR & 84" CA)

KNAPHEIDE SINCE 1848

Specifications subject to change without notice

BODY

Knapheide 6132DLHH-60J

- o 11' crane body with torq-isolator crane support system with torsion box understructure
- o A-40 galvanneal steel compartments and doors with 3/16" tread plate floor and 1/8" tread plate tops and backs that are full seam continuous welded
- o Compartment floors and end panels are 12 gauge steel with 14 gauge double panel, hat section reinforced compartment doors
- Body is completely immersed in Knapheide's electropheposition prime paint system for superior corrosion resistance
- o (6) Recessed cargo D-ring tie downs installed in floor with a 6,000 maximum capacity
- o (2) Heavy duty aluminum grab handles located on both sides at the rear of the body
- o LED S/T/T lights, clearance lights, and backup lights located at the rear
- 24" Work surface bumper with through compartments operated by stainless steel T-handles
- Vise plate located on work surface bumper
- o Pintle mount plate mounted below work surface bumper
- o (2) Grip strut flex steps mounted on the bottom of the work surface bumper on both sides
- 16" High double panel slam tailgate with center latch and flat space for tailgate graphics
- o Knapliner commercial grade spray-on bed liner applied to cargo floor, sides, compartment tops, bulkhead, and tailgate

CRANE

• Stellar 10621 Crane

- o 55,000 ft.-lbs. with 10,000 maximum capacity and 21' hydraulic reach
- o Planetary winch at 60'/minute speed with 7/16" cable and double-acting cylinders with integral holding valves and filters
- o Crane hook, snatch block, anti-two block device, boom support, RF wireless remote with backup pendant control, and control panel included
- Crane includes PTO, hydraulic pump for crane, hydraulic reservoir, and hydraulic shutdown

AIR COMPRESSOR

• Boss 35 CFM Compressor

O Hydraulic rotary screw compressor with Reelcraft 50' x ½" hose reel and roller fairlead through the curb side rear compartment

o FLR system and de-icer included with compressor

COMPARTMENTS

- 60" High compartments with stainless steel 3 point T-handles
 - O Street side front vertical compartment has a 7 drawer unit with (3) 3" high drawers, (3) 5" high drawers, and (1) 7" drawer
 - o Curb side front vertical compartment has (2) gas bottle retainers with both the top and bottom panels vented for air circulation
 - O Street side 2nd vertical compartment has (2) adjustable, 250 lb. maximum load capacity divider shelves with (4) dividers each
 - Curb side 2nd vertical compartment has (2) adjustable, 250 lb. maximum load capacity divider shelves with (4) dividers each
 - Street side horizontal compartment has parts storage containers
 - o Curb side horizontal compartment has bolt-in divider shelf with (8) dividers
 - O Street side rear vertical compartment has (2) adjustable, 250 lb. maximum load capacity divider shelves with (4) dividers each
 - o Curb side rear vertical compartment has (1) fixed shelf

SECURITY

- Master Locking System
 - Secures one entire side of compartments with one easy motion and a padlock

CAB PROTECTOR

• Bolt on cab protector with fully punched window

AUXILIARY LIGHTING

• (4) Halogen work lights installed

OUTRIGGERS

- (2) Outriggers installed
 - o (2) Hydraulic out and hydraulic down located at the rear

BACK UP ALARM

- 97db audible alarm
 - o Audible alarm engages when vehicle is put into reverse