

SPREADER SPECIFICATIONS




PRO-CASTER™



SPEED-CASTER™ 2



LOW PROFILE 2500



PRO-CASTER™ SPREADER SPECIFICATIONS

Body Side Length	Hopper Construction	Dimensions Overall Length x Width x Height	Hopper Weight in lbs (Gas Models)	Capacity Struck cu yds	Capacity Rounded cu yds	Spreading Width	Power Unit Options			Vehicle Application
							10.5 HP I/C Briggs & Stratton	11 HP I/C Honda	Hydraulic*	
8'	12 gauge steel	115" x 50 ³ / ₄ " x 32"	750	2.0	2.5	2' - 40'	X	X		3/4 and 1 Ton Pick-up Trucks (over 8500 lbs. GVWR)
8'	14 gauge SS	115" x 50 ³ / ₄ " x 32"	700	2.0	2.5	2' - 40'	X	X	X	
10'	12 gauge steel	139" x 58" x 37 ¹ / ₂ "	1000	3.3	4.1	2' - 40'	X		X	Dump Body or Flat Bed Trucks (over 15,000 lbs. GVWR)
10'	12 gauge SS	139" x 58" x 37 ¹ / ₂ "	1000	3.3	4.1	2' - 40'		X	X	
SS--Stainless Steel										

POLY-CASTER™ SPREADER SPECIFICATIONS

Body Side Length	Hopper Construction	Dimensions Overall Length x Width x Height	Hopper Weight In lbs	Capacity cu yds	Spreading Width	Spinner Size	Conveyor Width	Materials	Vehicle Application
7'	Polyethylene	108" x 63" x 44"	591	1.5	2' - 40'	15-1/2" Poly	16-3/4"	Sand & Salt	3/4- & 1-Ton
8'	Polyethylene	117" x 63" x 44"	660	1.8	2' - 40'	15-1/2" Poly	16-3/4"	Sand & Salt	3/4- & 1-Ton
8'	Polyethylene	117" x 63" x 51"	734	2.5	2' - 40'	15-1/2" Poly	16-3/4"	Sand & Salt	Dump Body or Flatbed Trucks

TAILGATE SPREADER SPECIFICATIONS

Tailgate Spreader	Spreader Construction	Approximate Wt. in lbs Empty	Capacity cu ft	Spreading Width	Dimensions H x W x L	Motor Size	Spinner Size	Materials	Vehicle Application
SPEED-CASTER™ 2 (2-Stage)	Polyethylene	235 w/o mount	10	5' - 20'	46" x 46" x 24"	1/3 HP	15 ¹ / ₂ "	Sand & Salt	3/4 & 1 Ton
Model 500 Low Profile	Polyethylene	75 with mount	5	3' - 30'	34" x 39" x 21"	1/3 HP	10"	Salt	Vehicles with Class III hitch
Model 1000 Low Profile	Polyethylene	105 w/o mount	8	3' - 30'	35" x 50 ¹ / ₂ " x 19 ¹ / ₂ "	1/3 HP	10"	Salt	Full Size Trucks
Model 2500 Low Profile	Polyethylene	105 with mount	8.5	3' - 30'	40" x 50" x 25"	1/3 HP	15"	Salt	Full Size Trucks



Fisher Engineering reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Fisher Engineering or the vehicle manufacturer may require or recommend optional equipment for spreaders. Do not exceed vehicle ratings with a spreader. This product is manufactured under the following



US patents: 5,375,773; 5,501,405; 7,400,058; CAN patent 2,126,035; and other patents pending. Fisher Engineering offers a limited warranty for all spreaders and accessories. See separately printed page for this important information. The following are registered(®) or unregistered(™) trademarks of Douglas Dynamics, L.L.C.: FISHER®, POLY-CASTER™, PRO-CASTER™, SPEED-CASTER™, SPEED-CASTER™ 2, SWING AWAY®.

FISHER ENGINEERING • 50 GORDON DRIVE • ROCKLAND, MAINE 04841 • www.fisherplows.com

All rights reserved.

Part # 50856

Ⓓ A SUBSIDIARY OF DOUGLAS DYNAMICS, L.L.C.

© 2010 Douglas Dynamics, L.L.C.

2/10 PRINTED IN U.S.A.