



Standard Specifications

- 96" Overall Width
- All Wheel Electric Brakes
- Break Away with Gel Cell Battery with Charge Unit
- DOT Approved LED Lighting
- 7 Way RV Style Flatblade Wire Plug Connector
- 3" Lunette Eye 4-Bolt Adjustable Coupler (4-Positions on 1/2" Plate)
- (2) 3/8" x 36" Safety Chains
- Drop Leg Jack 12,000# Side Wind
- 10 GA Formed Fenders
- 6" Channel Crossmembers
- Open Floor Pan
- 24" High, Full-Width Removable Bulkhead
- (4) 96" Pipe Bolsters with 24" Drop-In End Posts
- (4) Fixed Ratchets with 4" x 27' Nylon Straps
- Breaker Bar with Holder
- (2) 5" x 8" Rubber Wheel Chocks with Holders
- Two Part Polyurethane Primer and Paint
- Steel is Prepped, Primed, Painted, and Baked



Model Specific Standards

IGT 100

- 10" Channel Frame
- Rear Telescoping
- 30' Bulkhead to Bumper Retracted Length
- 38' Bulkhead to Bumper Extended Length
- (2) 7,000# Slipper Spring Axles 8-Bolt with ST235/80R16 Load Range E Tires on Silver Modular Wheels

IGT 200

- 10" Channel Double Boxed Mainframe with 6" Channel Tongue
- Front and Rear Telescoping
- 32' Bulkhead to Bumper Retracted Length
- 45' Bulkhead to Bumper Extended Length
- (2) 10,000# Slipper Spring Single Wheel Axles 8-Bolt with 215/75R17.5 Load Range H Tires on Solid Steel Wheels



Base Models
IGT 100 Telescoping Pipe Trailer
IGT 200 Telescoping Pipe Trailer

Axle Options (GAWR)
14,000# ILO 20,000# - (2) 7,000# Slipper Spring Axles 8-Bolt w/ ST235/80R16 E Tires
20,000# Dual Wheels ILO 20,000# Single Wheels - (2) 10,000# Slipper Spring Axles 8-Bolt w/ ST235/80R16 E Dual Wheels

Tire Options
ST235/80R16 E on 8-Bolt Silver Modular Wheel (Cap: 3520 #) (Spare - Includes Carrier)
215/75R17.5 H on 8-Bolt Solid Steel Wheel (Cap: 4805 #) (Spare - Includes Carrier)
ST235/80R16 E on 8-Bolt Budd Wheel (Cap: 2835 #) (Spare - Includes Carrier)

Jack Options
(2) 12,000# Drop Leg Single Speed Side Wind Jacks
(2) 12,000# Drop Leg Two Speed Side Wind Jacks

Coupler Option
Coupler 2 5/16" Ball ILO 3" Lunette Eye

Tool Box Options
Expanded Metal Tool Storage in Tongue
Add Lockable Lid to Expanded Metal Tool Storage
Tool Box Steel 14" x 16" x 36"

Miscellaneous Options
96" Pipe Bolster with 24" Drop-In End Posts (Additional)
96" Pipe Bolster with (2) 21" Sliding Stanchions ILO Standard
96" Pipe Bolster with (2) 21" Sliding Stanchions (Additional)
4" Fixed Ratchet (Additional)
4" x 27' Binder Strap (Additional)
Breaker Bar Holder (Additional)
Breaker Bar (Additional)
Aluminum Stop/Turn/Tail Light Bar for Rear with Securement Strap
Wire Plug 6 Prong Socket at Rear for Light Bar
Wheel Chock 7 1/2" x 7 1/2" Rubber ILO Standard
Wheel Chock Holder for 7 1/2" x 7 1/2" ILO Standard
Wheel Chock 6" x 9" Galvanized ILO Standard
Wheel Chock Holder for 6" x 9" ILO Standard
Additional Wheel Chock - Specify Type
Additional Wheel Chock Holder
Wire Plug 6 Pin Round ILO Standard
Wire Plug 7 Pin Round ILO Standard
Solar Charger for Breakaway Battery
Breaker Box with 15-Amp Breakers
Galvanize Trailer