

**Detachable**

# Chipper Body



Permanent Mount and Switch-N-Go Versions Available

### Chipper Body Specifications:

	STANDARD DUTY	MEDIUM DUTY	HEAVY DUTY
Floor Material	12 ga	12 ga	3/16"
Sides/Front/Tailgate	12 ga	12 ga	12 ga
3" Cross Members	16" Centers, structural	16" Centers, structural	16" Centers, structural
Top Rail	3" x 3" x 1/8" box tubing	3" x 3" x 1/8" box tubing	3" x 3" x 1/8" box tubing
Side Posts	11' and over bodies, 1 post per side; 12ga material	2-3 posts per side; 12ga material	Posts 30" - 36" centers; 12ga material
Rear Corner Posts	7 ga	7 ga	7 ga
Tailgate	Formed top with 2" x 2" x 1/8" tubular frame work	Formed top with 2" x 2" x 1/8" tubular frame work	3" x 3" x 1/8" vertical gate tubes, 10ga formed cross tubes
Available Side Heights	39", 51"	39", 51"	36", 48"
Roof	Constructed of 12ga sheets 24" high, Top supports 2" x 2" x 3/16" Angle, Mesh Vents on both sides		

Specifications are subject to change. With or without notice. Not warranted for any specific purpose.

**Features:**

Rear Gate - Single Side Swing or Double Barn Door Styles  
 Barn Door Shown to Right



Distributed by:

Switch-N-Go™  
 3550 Perry Hwy  
 Hadley, PA 16130  
 888-311-0867  
 www.switchngo.com



A Deist Industries, Inc. Company