

Skid-Steer Specifications

Model	Blade			Trip Springs	Ribs	Angling Rams	Plowing Width (full angle)	Approx. Weight	Wear Shoes	Cutting Edge
	Width	Height	Guage							
XBLADE	8'	31"	12	4	10	1.5" x 12"	7' 1"	790 lbs.	Optional	1/2" x 6" optional
XBLADE	9'	31"	12	4	10	1.5" x 12"	7' 11"	835 lbs.	Optional	1/2" x 6" optional
HD SERIES	7' 6"	29"	12	3	8	1.5" x 12"	6' 7"	630 lbs.	Standard	1/2" x 6" optional
HD SERIES	8'	29"	11	4	8	1.5" x 12"	7' 1"	717 lbs.	Standard	1/2" x 6" optional
HD SERIES	8' 6"	29"	11	4	8	1.5" x 12"	7' 6"	731 lbs.	Standard	1/2" x 6" optional
HD SERIES	9'	29"	11	4	8	1.5" x 12"	7' 11"	745 lbs.	Standard	1/2" x 6" optional
HD2	7' 6"	29"	12	3	10	1.5" x 12"	6' 9"	684 lbs.	Optional	3/8" x 6 steel
HD2	8'	29"	12	4	10	1.5" x 12"	7' 2"	734 lbs.	Optional	1/2" x 6" steel
HD2	8' 6"	29"	12	4	10	1.5" x 12"	7' 7"	750 lbs.	Optional	1/2" x 6" steel
HD2	9'	29"	12	4	10	1.5" x 12"	8' 1"	770 lbs.	Optional	1/2" x 6" steel
HDX	8'	29"	14	4	8	1.5" x 12"	7' 2"	861 lbs.	Optional	1/2" x 6" steel
HDX	9'	29"	14	4	8	1.5" x 12"	8' 1"	902 lbs.	Optional	1/2" x 6" steel

