

HIGH COUNTRY EXPRESSWAY

S T A N D A R D F E A T U R E S

1. Deep "C" A-Frame
2. [3] Adjustable Pitch Settings
3. 5" x 5" x 3/8" HD Square Tube Table, 90" wide Push Frame, and Massive 3-1/2" Round Pivot Bushing
4. [2] Telescopic Trip Bars, Compression (shown) or Extension Trip Springs and [4] 3" Poly Bushings for Return Trip Cushion
5. [5] Table to Moldboard Hook-Up Points with 1-1/2" Thick Ribs, 3" Bearing Surface and 1-1/4" Pins
6. 7" x 4" x 1/2" Fully Boxed Bottom Angle
7. Extended Roll Moldboard Continuously Welded



BASE MODEL 1&1EW4053MC1 SHOWN

Bonnell High Country Expressway Snow Plows are designed for removing snow at high-speeds in rural areas and interstate highways. The standard extended roll moldboard is designed to move the snow to the discharge end of the plow more efficiently. This prevents the snow from blowing over the top of the plow. This plow produces the same results when plowing to the left or to the right.

Bonnell's many standard features are what set us apart from our competition. These features, outlined above, include the 7" x 4" x 1/2" fully boxed bottom angle which adds strength to keep the moldboard from bending. We

also insert a 3" x 3" poly bushing into the top and bottom of both trip bars to absorb shock from tripping. The poly bushing provides cushion, making hitting an obstruction less intense and safer on the driver, plow, truck and the road.

All High Country Plows include an automatic safety feature which allows the moldboard to trip forward when the blade encounters an obstruction. After the obstruction is cleared, heavy-duty springs return the moldboard to its plowing position. This minimizes damage to the streets, plow, truck and driver.

HC Expressway Snow Plow Specifications


MODEL NUMBER	CUTTING EDGE LENGTH	OVERALL LENGTH	CENTER HEIGHT	DISCHARGE END HEIGHT	DISCHARGE END OVERHANG	NUMBER OF SPRINGS (EXTENSION)	CUTTING SWATH @ 35°	APPROXIMATE WEIGHT OF BASE UNIT
10EW3648MX1	10'0"	13'8"	36"	48"	14"	6	8' 2"	2,290 LBS.
11EW3649MX1	11'0"	14'8"	36"	49"	15"	6	9' 0"	2,367 LBS.
12EW3650MX1	12'0"	15'8"	36"	50"	16"	6	9' 9"	2,454 LBS.
10EW4052MX1	10'0"	13'8"	40"	52"	16"	6	8' 2"	2,360 LBS.
11EW4053MX1	11'0"	14'8"	40"	53"	17"	6	9' 0"	2,440 LBS.
12EW4054MX1	12'0"	15'8"	40"	54"	19"	6	9' 9"	2,529 LBS.
10EW4760MX1	10'0"	13'8"	47"	60"	18"	6	8' 2"	2,480 LBS.
11EW4761MX1	11'0"	14'8"	47"	61"	19"	6	9' 0"	2,558 LBS.
12EW4762MX1	12'0"	15'8"	47"	62"	20"	6	9' 9"	2,652 LBS.

All Models Come as Base Units without running gear, lifting assembly and plow hitching method.


Moldboard Thickness:	10 Gauge
Moldboard Reinforcing:	(7) - ½" x 3" Ribs
Adjustable Moldboard Pitch Settings:	35°, 25° or 15° off vertical
Lower Reinforcing Angle:	7° x 4" x ½"
Reversing Frame:	5" x 3/8" Wall Front Posh Tube
Reversing Cylinders:	4" Bore x 12" Stroke (2" Rod) Double Acting
Reversing Limits (left & right):	0 to 35 degrees
Plow to Table Hinge Points:	(5) 1-¼" Hinge Pins, Spanning 90"
Cutting Edge:	⅝" x 6" High Carbon Steel Std. Punch
Pivot Pin:	1-½" Grade 8 Bolt
Cylinder Pins:	1-¼" C1045 Steel Pins

The Bonnell HC Straight is available in multiple unique configurations, including:


10-Gauge Steel Construction with Extension Springs (EWMX1)




10-Gauge Steel Construction with Compression Springs (EVMC1)



UHMW Poly Construction with compression trip (EPMC1)



10-Gauge Steel Construction with Torsion Trip Edge (EWTT1)



1385 Franklin Grove Rd. • Dixon, IL 61021 • www.bonnell.com
(815) 284-3819 • (800) 851-9664 • Fax (815) 284-8815


Bonnell Industries reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used herein.
© 2006 Bonnell Industries, Inc.



High Country Options:


Plow Lift Options

- Chain
- Level Raise Lift System™
- Chain and Saddle
- Cable Wrap



Plow Hook-Up Options

- Quick Attach Loop
- Swivel Bar with Push Ears (1-¼" pins @ 30.5")
- Husting Style
- Custom Assembly



Running Gear Options


- Standard-Duty Mushroom Shoes
- Heavy-Duty Mushroom Shoes
- Heavy-Duty Even Wear Shoes
- Carbide Even Wear Shoes
- 10" Steel Caster (Kingpinless) Wheels
- 5.70 x 8.0 Pneumatic Tires*
- Foam-Filled Rubber Tires*

*Should not be used with Cable Wrap Lift Assemblies



Moldboard Options

- ¾" Bottom Angle
- 7-Gauge Steel Construction
- Trimmed Ears
- Extra Ribs
- Special Sizes Available



Tripping Options

- Extension Trip Moldboard
- Compression Trip Moldboard
- Torsion Trip Cutting Edge
- Dual Trip Moldboard & Cutting Edge




Table Options


- Extended Push Frame
- Manual Reverse

Cutting Edge Options

- High Carbon Steel
 - Rubber
 - UHMW Poly
 - Carbide Insert with Cover Blade
 - Flame Hardened
 - PolarFlex Systems
- All cutting edges available in various sizes

Other Options

- Cushion Valve
- Curb Shoes
- Blade Savers - Carbide
- Blade Guides
- Rubber Deflector
- Plow Stand
- Nirided Cylinders
- Extra Extension Trip Springs



Paint Options

- Special Paint Available