

KMT2-14 MECHANICS TRUCK
(25,999-33,000 GVWR & 120" CA)
Specifications subject to change without notice



BODY

- **Knapheide 6169DLHH-60J**
 - 14' crane body with torq-isolator crane support system with torsion box understructure
 - A-40 galvanized steel compartments and doors with 3/16" tread plate floor and 1/8" tread plate tops and backs that are full seam continuous welded
 - Compartment floors and end panels are 12 gauge steel with 14 gauge double panel, hat section reinforced compartment doors
 - Body is completely immersed in Knapheide's electroposition prime paint system for superior corrosion resistance
 - (6) Recessed cargo D-ring tie downs installed in floor with a 6,000 maximum capacity
 - (2) Heavy duty aluminum grab handles located on both sides at the rear of the body
 - LED S/T/T lights, clearance lights, and backup lights located at the rear
 - 24" Work surface bumper with through compartments operated by stainless steel T-handles
 - Vise plate located on work surface bumper
 - Pintle mount plate mounted below work surface bumper
 - (2) Grip strut flex steps mounted on the bottom of the work surface bumper on both sides
 - 16" High double panel slam tailgate with center latch and flat space for tailgate graphics
 - Knapliner commercial grade spray-on bed liner applied to cargo floor, sides, compartment tops, bulkhead, and tailgate

CRANE

- **Stellar 10621 Crane**
 - 55,000 ft.-lbs. with 10,000 maximum capacity and 21' hydraulic reach
 - Planetary winch at 60'/minute speed with 7/16" cable and double-acting cylinders with integral holding valves and filters
 - Crane hook, snatch block, anti-two block device, boom support, RF wireless remote with backup pendant control, and control panel included
 - Crane includes PTO, hydraulic pump for crane, hydraulic reservoir, and hydraulic shutdown

AIR COMPRESSOR

- **Boss 35 CFM Compressor**
 - Hydraulic rotary screw compressor with Reelcraft 50' x 1/2" hose reel and roller fairlead through the curb side rear compartment
 - FLR system and de-icer included with compressor

COMPARTMENTS

- **60" High compartments with stainless steel 3 point T-handles**
 - Street side front vertical compartment has a 7 drawer unit with (3) – 3" high drawers, (3) – 5" high drawers, and (1) – 7" drawer
 - Curb side front vertical compartment has (2) gas bottle retainers with both the top and bottom panels vented for air circulation
 - Street side 2nd vertical compartment has (2) adjustable, 250 lb. maximum load capacity divider shelves with (4) dividers each
 - Curb side 2nd vertical compartment has (2) adjustable, 250 lb. maximum load capacity divider shelves with (4) dividers each
 - Street side 3rd vertical compartment has (2) adjustable, 250 lb. maximum load capacity divider shelves with (4) dividers each
 - Curb side 3rd vertical compartment has (2) adjustable, 250 lb. maximum load capacity divider shelves with (4) dividers each
 - Street side horizontal compartment has parts storage containers
 - Curb side horizontal compartment has bolt-in divider shelf with (8) dividers
 - Street side rear vertical compartment has (2) adjustable, 250 lb. maximum load capacity divider shelves with (4) dividers each
 - Curb side rear vertical compartment has (1) fixed shelf

SECURITY

- **Master Locking System**
 - Secures one entire side of compartments with one easy motion and a padlock

CAB PROTECTOR

- **Bolt on cab protector with fully punched window**

AUXILIARY LIGHTING

- **(4) Halogen work lights installed**

OUTRIGGERS

- **(2) Outriggers installed**
 - (2) Hydraulic out and hydraulic down located at the rear

BACK UP ALARM

- **97db audible alarm**
 - Audible alarm engages when vehicle is put into reverse