

With enhanced strength and stability for higher crane loads, numerous configuration possibilities, and a body rating of 75,000 ft-lb (11.4 tm), the Dominator II mechanics truck offers exceptional performance in virtually any industry. With the Dominator II mechanics truck, you don't have to bring your equipment into the shop for service, because the shop comes to you.

> BASE BODY SPECIFICATIONS

Body Size	11' (3.4 m)	13' (3.9 m)	14' (4.3 m)	14' (4.3 m)	14' (4.3 m)				
Body Configuration⁴	LH & RH STD	RF RSD	LF & RF RSD	LF AR, RF RSD	ALL RSD	RF RSD	LF & RF RSD	LS AR, RF RSD	ALL RSD
Body Rating	75,000 ft-lb (11.4 tm)								
Body Weight ^{1,3}	3722 lb (1688.3 kg)	3789 lb (1718.7 kg)	3845 lb (1744.1 kg)	3883 lb (1761.3 kg)	3897 lb (1767.5 kg)	4205 lb (1907.4 kg)	4439 lb (2013.5 kg)	4502 lb (2042.1 kg)	4553 lb (2065.2 kg)
Body Width	96" (2.4 m)								
GVWR	19,500-33,000	19,500-33,000	19,500-33,000	26,000-33,000	26,000-33,000	26,000-33,000	26,000-33,000	26,000-33,000	26,000-33,000
Storage Capacity ³	141.5 ft ³ (4.0 m ³)	146.6 ft ³ (4.2 m ³)	151.8 ft ³ (4.3 m ³)	159.7 ft ³ (4.5 m ³)	164.9 ft ³ (4.7 m ³)	179.0 ft ³ (5.1 m ³)	197.1 ft ³ (5.6 m ³)	210.7 ft ³ (6.0 m ³)	215.4 ft ³ (6.1 m ³)
Angle of Departure	13°	13°	13°	13°	13°	13°	13°	13°	13°
Chassis CA ²	84" (2.1 m)	108" (2.7 m)	120" (3.0 m)	120" (3.0 m)	120" (3.0 m)				
Max. IMT Crane Model	10000 30'	10000 30'	10000 30'	10000 30'	10000 30'	10000 30'	10000 30'	10000 30'	10000 30'

¹ Includes doors, side packs, workbench. 2 Does not include welder deck. 3 Body weight and storage capacity are estimated based on product configuration.

⁴ Standard (STD) = 52", Raised (RSD) = 60"



> STANDARD FEATURES

- · IMT Patented Inverted A-Frame Design
- Three-Point Access Package
- Multiplex Electrical System with Programmable Logic
- IMT Compartment Coating (VOC-compliant polyurethane modified multicolor spray finish)
- Workbench Bumper

> OPTIONS

- · High-Intensity LED Lighting Package
- Axalta Bedliner
- IMT SiteStar® Lube Skid
- Drawer Sets, Adjustable Shelves
- Stabilizers
- Workbench Vises and Vise Plates
- **Energy-Absorbing Boom Support**
- · Compartment Pressurization System
- Compressed Air and Welding Systems
- Headache Rack
- Telescopic Roof
- Master Locks

> COMPATIBLE IMT CRANES

ELECTRIC HYDRAULIC

6006i · 3203i • 10000 · 7500 · 2820 · 1015

5005i · 2020E 8600 · 6000 · 2020

4004i · 1015E



REAR ACCESS PACKAGE

Featuring an extended handle for an easy grip and an extra step, the standard rear access package improves accessibility and is available curbside and roadside.



HIGH-INTENSITY LED LIGHTING

LED light bars provide superior light penetration for enhanced visibility.



BODY SUBSTRUCTURE

Patented A-Frame design with integrated crane box is engineered for maximum strength and weight reduction.

NOTHING SAYS COMMITMENT LIKE THE DIAMOND.™

Iowa Mold Tooling Co., Inc. | 500 Highway 18 West | Garner, Iowa 50438 | 800-247-5958 | imt.com







An Oshkosh Corporation Company