

ISUZU



DuraBOX

Dejana's DuraBox Bodies are designed for cab/chassis applications and have been engineered with a variety of heavy-duty features to provide years of dependable service. A wide range of sizes and configurations are also available to fit almost any chassis requirement from 10' to 26' in length and up to 102" of interior height.

DuraBox Bodies are available as either aluminum sheet and post (up to 26') or FRP (up to 24'). The aluminum design features .040" pre-painted aluminum sheet with galvanized "Z" posts on 16" centers, 2" spacing on seams, and 4" on ribs. Fiberglass Reinforced Plywood (FRP) sidewalls are also available that provide a smooth, clean exterior look that's great for graphics.

Units come standard with a 10" aluminum diamond plate radius to protect the front edge from damage and heavy-duty extruded aluminum corners. Rear posts are manufactured with 4" x 5" heavy-duty 12 Ga. steel that is specifically designed to accommodate railgate and liftgate installation. DE COMPARTING SART

Extreme duty composite roll up rear door with stainless steel/ aluminum hardware and 1" heavy-duty rollers Full width drop-step bumper Optional sliding ramp

EA Truck and 🗸 Utility Equipment

877.335.2621 www.Dejana.com 490 Pulaski Road • Kings Park, NY 11754

What Makes a Dejana DuraBOX Outlast the Competition... Standard Features Engineered for Maximum Strength and Durability





DEJANA

3)

- 3" I-Beam crossmembers, spaced on 16" centers
 - Beefy 4" x 5" Rear posts with 12 ga. galvanneal frame construction suitable for railgates & liftgates



- .040" pre-painted aluminum sheet with galvanized "Z" posts on 16" centers.
- 2 bolts into the extrusion to the I-beam for maximum rigidity.
- 2" rivet spacing on seams and 4" on ribs

Other Standard Features:

- Extreme duty composite roll up rear door. 3/8" plywood side walls
- Full width drop-step bumper
- Anti-snag roof bows on 24" centers
- 1/2" plywood front wall

Popular Options:

- Fiberglass Reinforced Plywood FRP
- Rear & side barn doors
- laminated hardwood floor
- Translucent roof

Exterior Length

4 bow ladder rack

- Complete underbody undercoat

• 10" diamondplate front radius to

protect from branches and debris.

• 5" radius aluminum corner castings

- Grab handles passenger and driver side
- Galvanized catwalk
- Sliding ramp
- 12" Rear crossover mirror
- Backup alarm



with an aviation grade adhesive. 4 Bow ladder rack (Optional)



- 2x6 tongue & groove pine (standard); Shiplap laminated hardwood floor (Optional)
- Floor flush with end plate
- Integral drain trough
- Incandescent marker lights
- Exterior lights meet FMVSS
- Dome light with switch in body

• 7 Horizontal wood slats in lieu of plywood walls

- 12" Apitong scuff plate
- 23" Threshold Plate
- Lift gate (See sales rep for applicable model)

1) Inside usable	lengths are based on rear roll
up doors; add 2	1/2" for rear barn doors.

2) Outside height dimensions include the roof crown but do not include the body long sills or chassis sleeper pads.

3) 102" wide bodies on NPR-HD, NPR-XD, NQR, NRR chassis require that the mirror brackets be modified at the port or by the dealership.

4) On NPR Diesel <= 14k GVW completed frontal area cannot exceed 79.9 sqf. Area >79.9 sqf to 84.8 sqf requires air roof fairing.

A DIVISION OF DOUGLAS DYNAMICS, L.L.C.

Length Dimensional Data 10' 12' 14' 16 18 26' (FTR Only) 20 22 24 10' 5" 12' 5" 14' 5" 16' 5" 18' 5" 20' 5" 22' 5" 24' 5" 26' 5" 15' 9½" 19' 9½" 21' 9½" 25' 9½" 9' 9½" 11' 9½" 13' 9½" 17' 9½" 23' 9½" **Interior Usable Length**

Height & Width D	Dimensional Data	Body Height & Width			Rear Door Opening	
Body Model	Outside Ht.	Inside Ht.	Outside wd.	Inside wd	Width	Height
ADB9678	85¼″	78¼″	96"	92¼″	88″	73³∕≋″
ADB9684	91¼″	84¼″	96"	92¼″	88"	79³⁄₃″
ADB9690	97¼″	90¼″	96"	92¼″	88"	85℁″
ADB9696	103¼″	96¼"	96"	92¼″	88"	91¾″
ADB96102	109¼″	102¼″	96"	92¼″	88″	97¾″

© 2018 Douglas Dynamics, LLC. All Rights Reserved.

